



opcjonalnie w komplecie: / optional included:



LED | IP54 | IK10 | Akku Li-ION | III | CE | T



- Moc 3,2W
- Strumień świetlny: 200lm
- Źródło światła SMD LED
- Kąt świecenia 110°
- Wysoki stopień szczelności IP54
- Klosz transparentny wykonany z poliwęglanu
- Gryf i kapa wykonane z gumy
- Obrotowy wieszak
- Wyłącznik elektroniczny w ręczce
- Akumulator Li-Ion 3,6V 2,0Ah
- Czas ładowania: 4h
- Czas pracy: 4h
- Zasilacz µUSB 230V / 5V 1000mA (w opcji)
- Waga 0,3 kg
- Możliwość dokupienia i wymiany podzespołów

- Power: 3,2W
- Luminous flux: 200lm
- Light source: SMD LED
- Lighting angle 110°
- High ingress protection class IP54
- Polycarbonate prismatic diffuser
- Handle and cap made of rubber
- Rotating hook
- On/off switch in the handle
- Li-Ion 3,6V 2,0Ah battery
- Charging time: 4h
- Working time: 4h
- Charger µUSB 230V / 5V 1000mA (optional)
- Weight 0,3 kg
- Spare parts available

index	nazwa article	kl.ochronności protection class
890307	Spark SMD LED z zasilaczem µUSB / with µUSB charger	III
890314	Spark SMD LED	III